

Rec'd PCT/PTO

07 JAN 2004

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number  
WO 2004/007630 A1

(51) International Patent Classification<sup>7</sup>: C09K 3/00, (74) Agent: ANDERSSON, Rolf; Akzo Nobel Surface Chemistry AB, S-444 85 Stenungsund (SE).

(21) International Application Number: PCT/SE2003/001015

(22) International Filing Date: 17 June 2003 (17.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 0202198-8 15 July 2002 (15.07.2002) SE

(71) Applicant (for all designated States except US): AKZO NOBEL NV [NL/NL]; P.O. Box 9300, NL-6800 SB Arnhem (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): HELLSTEN, Martin [SE/SE]; Värsåddsvägen 4, S-444 05 Ödsmål (SE). OS-KARSSON, Hans [SE/SE]; Egnahemsvägen 3a, S-444 41 Stenungsund (SE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 2004/007630 A1

(54) Title: A DRAG-REDUCING AGENT FOR USE IN INJECTION WATER AT OIL RECOVERY

(57) Abstract: The present invention relates to the use of a drag-reducing agent in an amount of 50-400 ppm in water having an electrolyte content of 0.01-7% by weight. The drag-reducing agent comprises two zwitterionics, each comprising acyl containing surfactant and an anionic surfactant, where the hydrophilic group is a sulphate, a sulphonate or an ether sulphate. The water containing the drag-reducing agent is suitable to be used in injection water at oil recovery.

BEST AVAILABLE COPY